



HOME EFFICIENCY REBATE + UP TO \$10,600 IN HOME RENO REBATES

SPACE HEAT PUMP	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
Geothermal (Ground Source Heat Pump)*		
Install a ground source heat pump – full system. The system capacity must be ≤ 40 kW. ⁽¹⁾	\$6,500	\$5,000
Replace a ground source heat pump – heat pump unit only. The system capacity must be ≤ 40 kW. ⁽²⁾	\$4,000	\$3,000
Air Source Heat Pump*		
Install a complete new or replacement variable capacity cold climate air source heat pump (ccASHP) system, intended to service the entire home. Add or install a central or 3 head system. ⁽³⁾	\$6,500	\$5,000
Install a complete ENERGY STAR certified new or replacement air source heat pump (ASHP) system, intended to service the entire home. ⁽⁴⁾	\$5,250	\$4,000
Install a complete ENERGY STAR certified new or replacement air source heat pump (ASHP) system or a variable capacity cold climate air source heat pump (ccASHP) system. Add or install a two head system. ⁽⁵⁾	\$3,250	\$2,500

EXTERIOR WALL INSULATION	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
For adding insulation value of at least greater than R20 for 100% of building	\$6,750	\$5,000
For adding insulation value greater than R12 up to R20 for 100% of building	\$5,000	\$3,800
For adding insulation value of R7.5 up to R12 for 100% of building	\$4,500	\$3,300
Attic, walls, foundation walls, all require minimum 20% upgraded.		

EXPOSED FLOOR INSULATION	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
For adding insulation value of at least R20 for entire exposed floor area ⁽⁶⁾	\$455	\$350

WATER HEATING	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
Domestic Hot Water Heat Pump*		
Replace domestic water heater with an ENERGY STAR® certified domestic hot water heat pump. ⁽⁷⁾	\$1,300	\$1,000

WINDOWS & DOORS	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
Window/ Sliding Door		
Replace windows or sliding glass doors with ENERGY STAR® most efficient models: - U-Factor of 1.05 W/m ² K or less or - Energy Rating of 40 or more	\$325	\$250
Replace windows or sliding glass doors with ENERGY STAR® certified models: - U-Factor of 1.22 W/m ² K or less or - Energy Rating of 34 or more	\$175	\$125
Door		
Replace hinged doors, with or without sidelites or transoms with ENERGY STAR® certified models: - U-Factor of 1.22 W/m ² K or less or - Energy Rating of 34 or more	\$175	\$125

ATTIC INSULATION	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
Increase attic insulation to at least R50 from R12 or less	\$2,350	\$1,800
Increase attic insulation to at least R50 from greater than R12 up to R25	\$800	\$600
Increase attic insulation to at least R50 from greater than R25 up to R35	\$325	\$250
Attic, walls, foundation walls, all require minimum 20% upgraded.		

CATHEDRAL/FLAT ROOF INSULATION	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
Increase cathedral/flat roof insulation to at least R-28 from R12 or less	\$800	\$600
Increase cathedral/flat roof insulation to at least R-28 from greater than R12 up to R25	\$325	\$250
Upgrade uninsulated cathedral ceiling/flat roof to at least R20	\$800	\$600

MORE REBATES ON PAGE TWO →

HOME EFFICIENCY REBATE +

RENEWABLE ENERGY SYSTEMS	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	OWNER OCCUPIED ONLY	
Install solar panels (photovoltaic system) equal to or greater than 1.0 kW DC (Maximum: \$5,000)	\$1,000 per kW	\$1,000 per kW

RESILIENCY MEASURES	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	OWNER OCCUPIED ONLY	
Batteries connected to Photovoltaic systems to provide standby power for home	\$1,000	\$1,000
Roofing membrane—self-adhering roofing underlayment applied to entire roof	\$150	\$150
Foundation water-proofing	\$875	\$875
Moisture proofing of 100% of crawlspace floor, walls and headers	\$600	\$600

AIR SEALING	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	Achieve base target	\$725
Achieve 10% or more above base target	\$1,050	\$810
Achieve 20% or more above base target	\$1,300	\$1,000

BASEMENT INSULATION	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	For adding insulation value greater than R22 to 100% of basement	\$2,000
For adding insulation value of R10 to R22 to 100% of basement	\$1,400	\$1,050

BASEMENT SLAB INSULATION	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	For sealing and insulating at least 50% of the entire basement slab by a minimum of R3.5	\$550

BASEMENT HEADER INSULATION	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	For sealing and insulating at least 80% of the basement header to add a minimum R20	\$325

CRAWLSPACE INSULATION (including header area)	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	For adding insulation value greater than R22 to 100% of exterior crawl space wall area, including header	\$1,700

For adding insulation value of R10 to R22 to 100% of exterior crawl space wall area, including header	\$1,400	\$1,040
For adding insulation value greater than R24 to 100% of crawl space ceiling	\$1,050	\$800

Attic, walls, foundation walls, all require minimum 20% upgraded.

AUDIT REBATE	ENBRIDGE CUSTOMER	NON-ENBRIDGE CUSTOMER
	Included in the maximum allowed	\$600

For more information or for additional rebates that may be available in your area please contact your local Energy Werx representative today.



THE HOME ENERGY EXPERTS, SINCE 2008

705-479-1005 north@energywerx.ca

north.energywerx.ca

Grant rebates payable shall not exceed amount invoiced for their associated upgrades.

While people can participate multiple times (up to rebate \$\$ cap), the \$600 "audit cost" rebate is available only once. Insulation rebates are pro-rated based on the % of the total square footage that is improved.

*MURBs do not qualify for this measure

(1) - Open systems - Heating COPh \geq 3.6 with 10°C entering water - Cooling COPc \geq 4.75 with 15°C entering water - Closed loop systems - Heating COPh \geq 3.1 with 0°C entering water - Cooling COPc \geq 3.93 with 25°C entering water

(2) - Open systems - Heating COPh \geq 3.6 with 10°C entering water - Cooling COPc \geq 4.75 with 15°C entering water - Closed loop systems - Heating COPh \geq 3.1 with 0°C entering water - Cooling COPc \geq 3.93 with 25°C entering water

(3) The newly installed system must meet the following criteria: - Compressor must be of variable capacity with three or more distinct operating speeds, or continuously variable speed - Minimum total rated heating capacity at 8.3 °C of 3.52 kW (12,000 BTU/h) - HSPF (AHRI Climate Region Zone IV) \geq 10 - Central system or minimum three indoor heads for ductless - COP \geq 1.8 at -15 °C (5 °F) (at maximum capacity operation); - Capacity maintenance (Max -15 °C (5 °F)/Rated 8.3 °C (47 °F)) \geq 70%

(4) The newly installed system must meet the following criteria: - Minimum total rated heating capacity at 8.3 °C of 3.52 kW (12,000 Btu/h) - HSPF (AHRI Climate Region Zone IV) \geq 10 - Central ducted system or minimum three indoor heads for ductless units

(5) The newly installed system must meet the following criteria: - Minimum total rated heating capacity at 8.3 °C of 3.52 kW (12,000 Btu/h) - HSPF (AHRI Climate Region Zone IV) \geq 10 - Two indoor heads ductless unit in addition, the cold climate air source heat pump (ccASHP) system must meet the following criteria: - Compressor must be of variable capacity with three or more distinct operating speeds, or continuously variable speed - COP \geq 1.8 at -15 °C (5 °F) (at maximum capacity operation); - Capacity maintenance (Max -15 °C (5 °F)/Rated 8.3 °C (47 °F)) \geq 70%

(6) Minimum area of 11 square meters or 120 square feet.

(7) Energy efficiency performance and installation:

- Capacity \leq 55 gal - EF \geq 2.00 with FHR \geq 50 gallons per hour or UEF \geq 2.00 FHR \geq 45 gallons per hour

- Capacity > 55 gal - EF \geq 2.20 FHR \geq 50 gallons per hour or UEF \geq 2.20 FHR \geq 45 gallons per hour